

ARCIMOTO UN38.3 TRANSPORTATION TESTING

SCOPE OF WORK

Model Name: Battery-Module Assembly

Part number: 002128

REPORT NUMBER

103619246DET-001

ISSUE DATE [REVISED DATE]

29-October-2018 [NA]

PAGES

35

DOCUMENT CONTROL NUMBER

RT-L-AMER-DET-003



October 29, 2018

Client P.O. No.: 00191

Page 2 of 35

Attn: Mr. Gerrit Hurenkamp

Arcimoto, Inc. 2034 West 2nd Ave Eugene, OR 97402 Phone: (559) 321-1694

E-mail Address: gerrith@arcimoto.com

DATE RECEIVED: 08/30/2018

DATE TESTED: 09/25/2018 through 10/22/2018

WORK REQUESTED / APPLICABLE DOCUMENTS:

Per the client's request and in accordance with UN 38.3 6th Edition and our quotation number 00893903, dated 06/20/2018; perform Battery Testing as described below:

■ T1 – Altitude Simulation

- T2 Thermal Test
- T3 Vibration
- T4 Shock

DESCRIPTION OF TEST SAMPLES:

SAMPLE DESCRIPTION: Four (4) Lithium-Ion Battery-Module Assemblies

MANUFACTURER: Arcimoto

PART NUMBER: 002128

RATINGS: 51.8V, 183.4Ah, 9500Wh

SPECIFICATION SECTIONS T1 through T4:

Four (4) Lithium-Ion Battery-Module Assemblies, sample numbers:

1 Cycle 25 cycles
- SN 1 - SN 3
- SN 2 - SN 4


Condition of Test Sample: Production

Testing Performed at:

Intertek 45000 Helm Street, Suite 150 Plymouth Twp., MI 48170

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 3 of 35



RESULT SUMMARY: The tested samples met the test requirements. See below breakout for tests performed.

Specification Section	Test Description	Results	
T1	Altitude Simulation	Pass	
T2	Thermal Test	Pass	
Т3	Vibration	Pass	
T4	Shock	Pass	

Lucas Salinas

Lucas Salinas

Engineer

October 29, 2018

Report No.: 103619246DET-001

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Report No.: 103619246DET-001

Page 4 of 35

EQUIPMENT LIST:

Asset #	Description	Manufacturer	Model	Serial#	Last Cal	Next Cal Due
160468	MULTIMETER	FLUKE	12	68151007	12/7/2017	12/7/2018
169029	SCALE	AEADAM	GFK 330aH	AE82650	7/9/2018	7/9/2019
162596	LXI DATA ACQUISITION / SWITCH UNIT	AGILENT	34972A	MY49008371	3/22/2018	3/22/2019
161279	ALTITUDE CABINET	ENTELA	N/A	N/A	VBU	VBU
161279.1	PRESSURE TRANSDUCER	FAIRCHILD	TA870212A	366027	12/1/2017	12/1/2018
373-207.1	ENVIRONMENTAL CHAMBER	ENVIROTRONICS	ENVIROTRONICS WPH1000-2-30- WC-	09158856	8/27/2018	8/27/2019
373-207P	Environmental Chamber	ENVIROTRONICS	WPH1000-2-30- WC-RUM	09158856	VBU	VBU
372-090	LXI DATA ACQUISITION / SWITCH UNIT	AGILENT	34972A	MY49003180	12/8/2017	12/8/2018
376-056	ACCELEROMETER	PCB	353B15	LW197020	8/10/2018	8/10/2019
376-041	SIGNAL PROCESSOR	VIBRATION RESEARCH	VR9500	951C711D	6/8/2018	6/8/2019
160122	VIBRATION SHAKER	UNHOLTZ- DICKIE	# 560	290	REF ONLY	REF ONLY
160112	VIBRATION AMP	UNHOLTZ- DICKIE	TA-117SA-560	1987	VBU	VBU
375-042	SIGNAL PROCESSOR	VIBRATION RESEARCH	VR9500	951394BE	2/2/2018	2/2/2019
161197	SHOCK MACHINE (asset for controller is 375-042)	AVCO	SM-220 MP	HP-0011	VBU	VBU
372-210	DIGITAL MULTIMETER	FLUKE	77 IV	38990065	9/12/2018	9/12/2019
376-009	ACCELEROMETER	PCB	350B03	46081	10/19/2017	10/19/2018
376-008	ACCELEROMETER	PCB	350B03	46080	11/22/2017	11/22/2018

^{*}VBU = "Verified Before Use"

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

October 29, 2018

Client P.O. No.: 00191

Page 5 of 35

SECTION 1

T1 – ALTITUDE SIMULATION

Date Received: 08/30/2018

Date(s) Tested: 09/25/2018 through 09/26/2018

Description of Samples:

Four (4) Lithium-Ion Battery-Module Assemblies, sample numbers:

1 Cycle 25 Cycles

- SN 1
- SN 2
- SN 4

Purpose:

This test simulates air transport under low-pressure conditions.

Test Procedure:

Prior to testing the voltage and mass were measured on each sample. The samples were then placed into an altitude cabinet, stored at a pressure of 11.6 kPa or less for six (6) hours at ambient temperature. After testing, the voltage and mass were measured on each sample.

Acceptance Criteria:

Cells and batteries meet this requirement if there is no mass loss, no leakage, no venting, no disassembly, no rupture and no fire and if the open circuit voltage of each test cell or battery after testing is not less than 90% of its voltage immediately prior to this procedure. The requirement relating to voltage is not applicable to test cells and batteries at fully discharged states.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Client P.O. No.: 00191 Page 6 of 35

T1 – ALTITUDE SIMULATION (cont'd)

Results:

The test samples conformed to the acceptance criteria; there was no mass loss, no leakage, no venting, no disassembly, no rupture, no fire and the open circuit voltage of each test sample after testing was not less than 90% of its voltage immediately prior to this procedure.

	T1 - Altitude Simulation							
Sample No.	Pre Conditioning Cycles	Voltage Pre Test (VDC)	Voltage Post Test (VDC)	% Change (Not Greater Than 10%)	Weight Pre Test (Grams)	Weight Post Test (Grams)	% Change (Not Greater Than 0.1%)	Meets requirement
1	1	58.0	57.9	0.172	53806	53808	-0.004	Pass
2	1	58.0	57.9	0.172	53988	53990	-0.004	Pass
3	25	58.0	58.0	0.000	53858	53858	0.000	Pass
4	25	58.1	58.0	0.172	53848	53848	0.000	Pass

Appendix:

Appendix A – Photographs

Appendix B – Altitude Simulation Graph

Disposition of Test Samples:

At the completion of testing, the samples continued to T2 – Thermal Test.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

October 29, 2018

Client P.O. No.: 00191

Page 7 of 35

SECTION 2

T2 – THERMAL TEST

Date Received: 08/30/2018

Date(s) Tested: 09/26/2018 through 10/08/2018

Description of Samples:

Four (4) Lithium-Ion Battery-Module Assemblies, sample numbers:

1 Cycle 25 Cycles

SN 1
SN 2
SN 4

Purpose:

This test assesses cell and battery seal integrity and internal electrical connections. The test is conducted using rapid and extreme temperature changes.

Test Procedure:

Prior to testing the voltage and mass were measured on each sample. The samples were placed into an environmental chamber and stored for twelve (12) hours at $72^{\circ}\text{C} \pm 2^{\circ}\text{C}$, followed by storage of equal time at a temperature of $-40^{\circ}\text{C} \pm 2^{\circ}\text{C}$. The maximum time interval between test temperature extremes was 30 minutes. This procedure was repeated 10 times, after which all samples were stored for 24 hours at ambient temperature. After testing the voltage and mass were measured on each sample.

Acceptance Criteria:

Cells and batteries meet this requirement if there is no mass loss, no leakage, no venting, no disassembly, no rupture and no fire and if the open circuit voltage of each test cell or battery after testing is not less than 90% of its voltage immediately prior to this procedure. The requirement relating to voltage is not applicable to test cells and batteries at fully discharged states.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 8 of 35

T2 - THERMAL TEST (cont'd)

Results:

The test samples conformed to the acceptance criteria; there was no mass loss, no leakage, no venting, no disassembly, no rupture, no fire and the open circuit voltage of each test sample after testing was not less than 90% of its voltage immediately prior to this procedure.

	T2 - Thermal Test							
Sample No.	Pre Conditioning Cycles	Voltage Pre Test (VDC)	Voltage Post Test (VDC)	% Change (Not Greater Than 10%)	Weight Pre Test (Grams)	Weight Post Test (Grams)	% Change (Not Greater Than 0.1%)	Meets requirement
1	1	57.9	57.5	0.691	53808	53792	0.030	Pass
2	1	57.9	57.5	0.691	53990	53976	0.026	Pass
3	25	58.0	57.6	0.690	53858	53848	0.019	Pass
4	25	58.0	57.6	0.690	53848	53836	0.022	Pass

There is no recorded data for the first temperature cycle as the Agilent was not set up until the 2^{nd} day of the test. The plan was to use Chamber Monitoring, but it was deemed too inconsistent, so the Agilent was added.

There is also no recorded data for the 9th and 10th cycles as the Agilent did not correctly record the 4th data pull. Only most recent 25000 lines of data were able to be recovered, so roughly 2.5 days of data were lost.

Appendix:

Appendix A – Photographs

Appendix C – Thermal Test Graph

Disposition of Test Samples:

At the completion of testing, the samples continued to T3 – Vibration.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Arcimoto, Inc.

Report No.: 103619246DET-001
October 29, 2018

Page 9 of 35

SECTION 3

T3 - VIBRATION

Client P.O. No.: 00191

Date Received: 08/30/2018

Date(s) Tested: 10/08/2018 through 10/15/2018

Description of Samples:

Four (4) Lithium-Ion Battery-Module Assemblies, sample numbers:

1 Cycle 25 Cycles

SN 1
SN 2
SN 4

Purpose:

This test simulates vibration during transport.

Test Procedure:

Prior to testing the voltage and mass were measured on each sample. The samples were firmly secured to the platform of the vibration machine without distorting the packs in such a manner as to faithfully transmit the vibration. The test samples were subjected to sinusoidal waveform with a logarithmic sweep between 7 Hz and 200 Hz and back to 7 Hz traversed in 15 minutes. This cycle was repeated 12 times for a total of three (3) hours for each of the three (3) mutually perpendicular mounting positions of the sample. One of the directions of vibration must be perpendicular to the terminal face.

The logarithmic frequency sweep is as follows: from 7 Hz a peak acceleration of 1g is maintained until 18 Hz is reached. The amplitude is then maintained at 0.8mm (1.6mm total excursion) and the frequency increased until a peak acceleration of 2g occurs (approximately 25 Hz). A peak acceleration of 2g is then maintained until the frequency is increased to 200 Hz. After testing the voltage and mass were measured on each sample.

Acceptance Criteria:

Cells and batteries meet this requirement if there is no leakage, no venting, no disassembly, no rupture and no fire and if the open circuit voltage of each test cell or battery after testing is not less than 90% of its voltage immediately prior to this procedure. The requirement relating to voltage is not applicable to test cells and batteries at fully discharged states.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Arcimoto, Inc. Report No.: 103619246DET-001

t P.O. No.: 00191 Page 10 of 35

T3 - VIBRATION (cont'd)

Results:

The test samples conformed to the acceptance criteria; there was no leakage, no venting, no disassembly, no rupture and no fire and the open circuit voltage of each test cell or battery after testing was not less than 90% of its voltage immediately prior to this procedure. The requirement relating to voltage is not applicable to test cells and batteries at fully discharged states.

	T3 - Vibration								
Sample No.	Pre Conditioning Cycles	Voltage Pre Test (VDC)	Voltage Post Test (VDC)	% Change (Not Greater Than 10%)	Weight Pre Test (Grams)	Weight Post Test (Grams)	% Change (Not Greater Than 0.1%)	Meets requirement	
1	1	57.5	57.400	0.174	53792	53800.000	-0.015	Pass	
2	1	57.5	57.400	0.174	53976	53982.000	-0.011	Pass	
3	25	57.6	57.600	0.000	53848	53854.000	-0.011	Pass	
4	25	57.6	57.600	0.000	53836	53844.000	-0.015	Pass	

Appendices:

Appendix A – Photographs Appendix D – Vibration Plots

Disposition of Test Samples:

At the completion of testing, the samples continued to T4 – Shock.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 11 of 35

October 29, 2018 Client P.O. No.: 00191

SECTION 4

T4 – SHOCK

Date Received: 08/30/2018

Date(s) Tested: 10/19/2018 through 10/22/2018

Description of Samples:

Four (4) Lithium-Ion Battery-Module Assemblies, sample numbers:

1 Cycle 25 Cycles

SN 1
SN 2
SN 4

Purpose:

This test simulates possible impacts during transport.

Test Procedure:

Prior to testing the voltage and mass were measured on each sample. The samples were secured to the testing machine by means of a rigid mount with support on all mounting surfaces of each test battery. Each sample was subjected to a half-sine shock of peak acceleration depending on the mass of the battery. The pulse duration shall be eleven (11) milliseconds. Table 1 provides the formulas below are provided to calculate the appropriate minimum peak accelerations.

Battery	Minimum peak acceleration	Pulse duration			
Small batteries	150 g _n or result of formula $Acceleration(g_n) = \sqrt{\frac{100850}{mass*}}$ whichever is smaller	6 ms			
	50 g _n or result of formula				
Large batteries	$Acceleration(g_n) = \sqrt{\left(\frac{30000}{mass*}\right)}$	11 ms			
	whichever is smaller				
* Mass is expressed in kilograms.					

Table 1: T4 – Shock Peak Acceleration Formula

The peak acceleration for these large battery packs is 23.6g.

Each sample was subjected to three (3) shocks in the positive direction followed by three (3) shocks in the negative direction of the three mutually perpendicular mounting positions. After testing the voltage and mass were measured on each sample.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 12 of 35

T4 - SHOCK (cont'd)

Acceptance Criteria:

Cells and batteries meet this requirement if there is no leakage, no venting, no disassembly, no rupture and no fire and if the open circuit voltage of each test cell or battery after testing is not less than 90% of its voltage immediately prior to this procedure. The requirement relating to voltage is not applicable to test cells and batteries at fully discharged states.

Results:

The test samples conformed to the acceptance criteria; there was no leakage, no venting, no disassembly, no rupture and no fire and the open circuit voltage of each test cell or battery after testing was not less than 90% of its voltage immediately prior to this procedure. The requirement relating to voltage is not applicable to test cells and batteries at fully discharged states.

	T4 - Shock							
Sample No.	Pre Conditioning Cycles	Voltage Pre Test (VDC)	Voltage Post Test (VDC)	% Change (Not Greater Than 10%)	Weight Pre Test (Grams)	Weight Post Test (Grams)	% Change (Not Greater Than 0.1%)	Meets requirement
1	1	57.400	57.480	-0.139	53800.000	53802.000	-0.004	Pass
2	1	57.400	57.480	-0.139	53982.000	53982.000	0.000	Pass
3	25	57.600	57.640	-0.069	53854.000	53854.000	0.000	Pass
4	25	57.600	57.610	-0.017	53844.000	53842.000	0.004	Pass

Appendices:

Appendix A – Photographs Appendix E – Shock Plots

Disposition of Test Samples:


At the completion of testing, the samples were returned to the client.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Report No.: 103619246DET-001

Page 13 of 35

APPENDIX A – PHOTOGRAPHS T1 – Altitude Simulation



Photograph 1: Altitude Simulation Setup

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Arcimoto, Inc. Report No.: 103619246DET-001

Page 14 of 35

APPENDIX A – PHOTOGRAPHS (cont'd) T2 – Thermal Test




Photograph 2: Thermal Test Setup

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 15 of 35

APPENDIX A – PHOTOGRAPHS (cont'd) T3 – Vibration



Photograph 3: Vibration Test Setup – Fore/Aft Direction




Photograph 4: Vibration Test Setup - Lateral Direction

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Report No.: 103619246DET-001

Page 16 of 35

APPENDIX A – PHOTOGRAPHS (cont'd) T3 – Vibration




Photograph 5: Vibration Test Setup - Vertical Direction


This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 17 of 35

APPENDIX A – PHOTOGRAPHS (cont'd) T4 – Shock



Photograph 6: Shock Test Setup –Fore/Aft, Positive Direction



Photograph 7: Shock Test Setup – Fore/Aft, Negative Direction

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 18 of 35

APPENDIX A – PHOTOGRAPHS (cont'd) T4 – Shock



Photograph 8: Shock Test Setup – Lateral, Positive Direction




Photograph 9: Shock Test Setup – Lateral, Negative Direction


This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 19 of 35

APPENDIX A – PHOTOGRAPHS (cont'd) T4 – Shock



Photograph 10: Shock Test Setup – Vertical, Positive Direction



Photograph 11: Shock Test Setup – Vertical, Negative Direction

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 20 of 35

APPENDIX B T1 – Altitude Simulation Graph




Figure 1: Altitude Simulation Graph; SN1-2




Figure 2: Altitude Simulation Graph; SN3-4

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 21 of 35

APPENDIX C T2 – Thermal Test Graph




Figure 3: Thermal Test Graph, Cycles 2-8; SN1-4




Figure 4: Thermal Test Graph, End of Cycle 10 and 24 hr Hold; SN1-4

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Report No.: 103619246DET-001

Page 22 of 35

APPENDIX D T3 – Vibration Plots




Figure 5: Vibration Plot - Fore/Aft Direction; SN1




Figure 6: Vibration Plot - Fore/Aft Direction; SN2

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Report No.: 103619246DET-001

Page 23 of 35

APPENDIX D T3 – Vibration Plots (cont'd)




Figure 7: Vibration Plot - Fore/Aft Direction; SN3




Figure 8: Vibration Plot - Fore/Aft Direction; SN4

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Report No.: 103619246DET-001

Page 24 of 35

APPENDIX D T3 – Vibration Plots (cont'd)




Figure 9: Vibration Plot - Lateral Direction; SN1




Figure 10: Vibration Plot – Lateral Direction; SN2

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Report No.: 103619246DET-001

Page 25 of 35

APPENDIX D T3 – Vibration Plots (cont'd)




Figure 11: Vibration Plot - Lateral Direction; SN3




Figure 12: Vibration Plot - Lateral Direction; SN4

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Report No.: 103619246DET-001

Page 26 of 35

APPENDIX D T3 – Vibration Plots (cont'd)




Figure 13: Vibration Plot - Vertical Direction; SN1




Figure 14: Vibration Plot – Vertical Direction; SN2

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Report No.: 103619246DET-001

Page 27 of 35

APPENDIX D T3 – Vibration Plots (cont'd)




Figure 15: Vibration Plot – Vertical Direction; SN3




Figure 16: Vibration Plot - Vertical Direction; SN4

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 28 of 35

APPENDIX E T4 – Shock Plots




Figure 17: Shock Plot -Fore/Aft, Positive Direction; SN1




Figure 18: Shock Plot -Fore/Aft, Positive Direction; SN2

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 29 of 35

APPENDIX E T4 – Shock Plots (cont'd)




Figure 19: Shock Plot -Fore/Aft, Positive Direction; SN3




Figure 20: Shock Plot -Fore/Aft, Positive Direction; SN4

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 30 of 35

APPENDIX E T4 – Shock Plots (cont'd)




Figure 21: Shock Plot -Fore/Aft, Negative Direction; SN1




Figure 22: Shock Plot -Fore/Aft, Negative Direction; SN2

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 31 of 35

APPENDIX E T4 – Shock Plots (cont'd)




Figure 23: Shock Plot -Fore/Aft, Negative Direction; SN3




Figure 24: Shock Plot -Fore/Aft, Negative Direction; SN4

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 32 of 35

APPENDIX E T4 – Shock Plots (cont'd)




Figure 25: Shock Plot - Lateral, Positive Direction; SN1-2




Figure 26: Shock Plot - Lateral, Positive Direction; SN3-4

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 33 of 35

APPENDIX E T4 – Shock Plots (cont'd)




Figure 27: Shock Plot - Lateral, Negative Direction; SN1-2




Figure 28: Shock Plot – Lateral, Negative Direction; SN3-4

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 34 of 35

APPENDIX E T4 – Shock Plots (cont'd)




Figure 29: Shock Plot - Vertical, Positive Direction; SN1-2




Figure 30: Shock Plot - Vertical, Positive Direction; SN3-4

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 35 of 35

APPENDIX E T4 – Shock Plots (cont'd)




Figure 31: Shock Plot – Vertical, Negative Direction; SN1-2




Figure 32: Shock Plot - Vertical, Negative Direction; SN3-4

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.